

Workplace Safety Card

Identification of the substance/mixture

Trade name

Løbsvæske acetone_heptan

Usage

Laboratorier

Emergency telephone

Call "Giftlinien" 8212 1212 (open 24 /7)

Hazards identification

Classification of the substance or mixture

Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 1, Aquatic Acute 1, STOT SE 3, Asp. Tox. 1, Flam. Liq. 2, Skin Irrit. 2 // H410, H336, H319, H315, H304, H225



Danger!

Hazards

Highly flammable liquid and vapour. (H225)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)
Very toxic to aquatic life with long lasting effects. (H410)

▼ Safety statements

General

-

Prevention

Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Wash exposed areas thoroughly after handling. (P264)

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. (P301+P310)

Response

Do NOT induce vomiting. (P331)

Storage

Store locked up. (P405)

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Additional labelling

-

Personal protective equipment



Generally

Only CE-marked personal protection equipment should be used.

Respiratory equipment

Recommended: Use in fumehood, -, -

Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

Hand protection

Recommended: Nitrile rubber. . Breakthrough time: > 60 minutes (Class 3)

Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.