

Workplace Safety Card

Identification of the substance/mixture

Trade name

Propan-2-ol (isopropanol)

Usage

NA

Emergency telephone

Call "Giftlinien" 8212 1212 (open 24 /7)

Hazards identification

Classification of the substance or mixture

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

**Danger****Hazards**

Highly flammable liquid and vapour. (H225)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

| | | |
|--------------------------|-------------------|---|
| Safety statements | General | - |
| | Prevention | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210). Wear eye protection. (P280). |
| | Response | If eye irritation persists: Get medical advice/attention. (P337+P313). In case of fire: Use alcohol-resistant foam/carbonic acid/powder/water mist/carbon dioxide/dry sand to extinguish. (P370+P378). |
| | Storage | Store in a well-ventilated place. Keep cool. (P403+P235). |
| | Disposal | Dispose of contents/container to an approved waste disposal plant. (P501). |

Additional labelling

Not applicable

Personal protective equipment

**Generally**

Use only CE marked protective equipment.

Respiratory equipment

Use in fumehood

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

Hand protection

Recommended: Nitrile rubber. Breakthrough time: > 120 minutes (Class 4)

Eye protection

Wear safety glasses with side shields.