

Workplace Safety Card

Identification of the substance/mixture

Trade name

zink- stang

Usage

NA

Emergency telephone

Call "Giftlinien" 8212 1212 (open 24 /7)

Hazards identification

Classification of the substance or mixture

Pyr. Sol. 1; H250
Water-react. 1; H260
Aquatic Acute 1; H400
Aquatic Chronic 1; H410

**Danger****Hazards**

Catches fire spontaneously if exposed to air. (H250)
In contact with water releases flammable gases which may ignite spontaneously. (H260)
Very toxic to aquatic life with long lasting effects. (H410)

Safety statements**General**

-
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Prevention

No smoking. (P210).

Response

Wear protective clothing/protective gloves/eye protection/face protection. (P280).
In case of fire: Use alcohol-resistant foam/carbonic acid/powder/water mist/carbon dioxide/dry sand to extinguish. (P370+P378).

Storage

IF ON SKIN: Immerse in cool water or wrap in wet bandages. (P302+P334).

Disposal

Store contents under . (P422).

Dispose of contents/container to an approved waste disposal plant. (P501).

Additional labelling

-

Personal protective equipment

**Generally**

Use only CE marked protective equipment.

Respiratory equipment

NA

Skin protection

No specific requirements.

Hand protection

Recommended: Nitrile rubber. Breakthrough time: > 480 minutes (Class 6)

Eye protection

No specific requirements.